

Digital pH Meter DPH-2

Cat.No.4320

- **Automatic Temperature Compensation!**
- **Waterproof, ideal for on-site use!**
- **Compact/portable design!**
- **Sturdy body design for electrode-protection**
- **Electrode can be cleaned with tap water**
(Use of deionized water will damage the electrode.)




Applications

- Food and beverage production control
- Brewing, fermentation, and food process control
- Agriculture industry for soil and hydroponics
- Cutting oils, alkaline washing liquids
- pH levels of fruit juices
- Quality control for aquacultures and aquariums
- pH levels of boiler liquids
- pH levels of alkaline liquid
- Other soluble solutions



Easy one handed operation.

Specifications

Measurement Range : 0.0~14.0pH
 Resolution : 0.1pH
 Measurement accuracy : ± 0.1 pH (2.0~12.0pH)
 Temperature compensation range : 0~50°C
 (Automatic Temperature Compensation)
 Calibration : 3-points (4.0, 7.0, and 10.0)
 Power supply : watch battery (LR44) : x 4
 Materials in contact with the solution :
 Main body-ABS resin/Electrode-PBT resin
 International Protection class : IP67
 Dimensions & weight : 4.5 x 3.0 x 16.3cm, 90g

All ATAGO refractometers are designed and manufactured in Japan.

HACCP GMP GLP

ATAGO products comply with HACCP, GMP, and GLP standards.

ATAGO CO., LTD.

Headquarters: 32-10, Honcho, Itabashi-ku, Tokyo 173-0001 Japan
 TEL: 81-3-3964-6156 FAX: 81-3-3964-6137
 overseas@atago.net http://www.atago.net/

ATAGO U.S.A., Inc.

12011 NE First Street, Bldg. C, Suite 110, Bellevue, WA 98005 U.S.A.
 TEL: 1-425-637-2107 FAX: 1-425-637-2110
 customerservice@atago-usa.com http://www.atago.net/USA/

ATAGO INDIA Instruments Pvt. Ltd.

A-501, Mangal Aarambh Business Centre, Near Kora Kendra, Off. S.V. Road, Borivali (West), Mumbai-400 092 India
 TEL: 91-22-2833-8038 / 8076 FAX: 91-22-2899-8164
 customerservice@atago-india.com



※Specifications and appearance are subject to change without notice.